

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
12 February 2004 (12.02.2004)


PCT

(10) International Publication Number  
**WO 2004/013009 A1**

- (51) International Patent Classification<sup>7</sup>: **B65D 37/00**
- (21) International Application Number:  
PCT/US2003/024484
- (22) International Filing Date: 6 August 2003 (06.08.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
60/401,397 6 August 2002 (06.08.2002) US
- (71) Applicant (for all designated States except US): **COHEN, Ben, Z.** [US/US]; 140 East 80th Street, New York, NY 10021 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **KELLY, Nigel** [US/US]; 60 Fulton Avenue, Rye, NY 10580 (US).
- (74) Agent: **BUDZYN, Ludomir, A.**; Hoffmann & Baron, LLP, 6900 Jericho Turnpike, Syosset, New York 11791 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: DROPPER BOTTLE AND ACCESSORIES THEREFOR



(57) Abstract: To overcome shortcomings of the prior art, the subject invention is provided which includes various dropper bottle designs and dropper bottle assemblies including accessories for dropper bottles. More specifically, certain embodiments use devices (10, 300) to restrict the amount the dropper bottle (12) is deformed in administering a dose; other embodiments rely on mechanical reduction of interior volume (without deformation of the dropper bottle (12) to administer a dose, such as with a displaceable piston (500, 602); and, yet, a further embodiment provides a valving arrangement (402, 404) to limit a dose. Features (200) are also included which aid in the alignment of the dropper bottle's nozzle to the eye, and a feature (102) is provided for protecting the user's eye from potential damage which can occur if a pointed nozzle (104) is brought into contact with the eye during alignment.

WO 2004/013009 A1



**Published:**

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

*For two-letter codes and other abbreviations, refer to the "Guide Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**DROPPER BOTTLE AND ACCESSORIES THEREFOR**

This application claims priority to U.S. Provisional Patent Application No. 60/401,397, filed August 6, 2002.

5           Conventional dropper bottles for administering ophthalmic fluid are well known in the prior art. The basic commercial design of such dropper bottles has remained fairly unchanged over the last several decades: a squeezable container is provided with a tapered dispenser that terminates in a discharge aperture. To administer ophthalmic fluid, the discharge aperture is aligned above a target eye and the bottle is squeezed to urge out a drop  
10 or dose of the fluid.

          Although the conventional design is widely used, it suffers from several drawbacks. Primarily, dose volume is difficult to repeatedly control, in part, because a proper amount of squeeze force is difficult to repeatedly apply to the dropper bottle. Also, accurate control  
15 over and targeting of dose placement are difficult to obtain.

**SUMMARY OF THE INVENTION**

          To overcome shortcomings of the prior art, the subject invention is provided which includes various dropper bottle designs and dropper bottle assemblies including accessories  
20 for dropper bottles. With certain aspects of the subject invention, improvements in the administration of eye drops is provided by adding accessories or modifications to conventional dropper bottles, so that doses and/or single drops may be administered in a repeatable and reliable manner. More specifically, certain embodiments restrict the amount

the dropper bottle is deformed in administering a dose; other embodiments rely on mechanical reduction of interior volume (without deformation of the dropper bottle) to administer a dose, such as with a displaceable piston; and, yet, a further embodiment provides a valving arrangement to limit a dose. Further features are included which aid in the  
5 alignment of the dropper bottle's nozzle to the eye, and also protect the user's eye from potential damage which can occur if a pointed nozzle is brought into contact with the eye during alignment. As will be appreciated by those skilled in the art, the various aspects and embodiments disclosed herein may be used singularly or in various combinations.

10 Unless indicated otherwise, any conventional dropper bottle design and component may be utilized with the subject invention. It should also be understood that reference to a "nozzle" does not require that a converging discharge passage be provided. Any shaped discharge passage can be utilized with the subject invention consistent with the following description. The subject invention is particularly well-suited for ophthalmic applications  
15 (i.e., dispensing of eye-related fluids).

These and other features of the subject invention will be better understood through a study of the following detailed description and accompanying drawings.

## 20 **BRIEF DESCRIPTION OF THE DRAWINGS**

Figures 1-3 show a dropper bottle assembly including a cradle for controllably deforming the dropper bottle in causing dose administration therefrom;

Figure 4 is a dropper bottle similar to that of Figures 1-3 but with a collar disposed  
25 about its nozzle;

Figure 5 is a dropper bottle similar to that of Figures 1-3 but with an angled nozzle;

Figures 6-8 show the assembly and operation of a webbed structure in a dropper bottle

5 for limiting deformation of the dropper bottle;

Figures 9-11 show a dropper bottle having a tube therein with a check valve ball; and,

Figures 12-16 show different piston configurations for reducing the interior volume of

10 a dropper bottle in causing dose administration therefrom.

#### **DETAILED DESCRIPTION OF THE INVENTION**

Several embodiments of the subject invention are directed to the problem that most current dropper bottles require the bottle to be deformed, e.g. squeezed, in order to generate  
15 pressure inside the bottle and, thereby, expel a dose or drop. This practice is problematic because the user is often unable to determine how hard to press the bottle, and for how long a period of time, so that a single drop is expelled. Usually, more than one drop is expelled, which may be wasteful and messy.

20 With reference to Figures 1-3, and in a first aspect of the subject invention, a cradle 10 is depicted which is formed to mount onto a dropper bottle 12 preferably by resiliently snapping onto the bottle 12 at the neck 14 and base 16. Preferably, the cradle 10 is formed of a resilient material, more preferably, a resilient thermoplastic. Mounting of the cradle 10 onto the neck 14 is facilitated by the provision of a hole 18 formed large enough to allow the  
25 bottle 12 to partially pass therethrough. In particular, the neck 14 of the bottle 12 may pass

through the hole 18; preferably, however, the hole 18 is sized to not allow the passage therethrough of the reservoir 20 of the bottle 12. Once the cradle 10 is mounted, the bottle neck 14 is preferably pushed off-center from the hole 18 (Figure 3) due to pressure exerted transversely by a portion 22 of cradle lever 24 against an outer wall 23 that defines the reservoir 20. The bottle 12 is further confined by side plate 11 of the cradle 10. The portion 22 presses the bottle 12 against inner surface 13 of the side plate 11. Preferably, the portion 22 is bent. In addition, the lower end 26 of the cradle 10 may seat in an indentation 28 in the base 16 of the bottle 12 and resiliently press thereagainst. As such, the cradle 10 preferably traps the bottle 12 at multiple points: at the hole 18; at the portion 22; at the inner surface 13; and at the lower end 26 of the cradle 10. As will be appreciated by those skilled in the art, the cradle 10 may be configured otherwise to mount onto the dropper bottle 12. The cradle 10 may be formed to be removable so as to be re-used with other dropper bottles or formed to be non-removably mounted to the dropper bottle, thus requiring to be discarded with a spent dropper bottle.

In use, free end 30 of the cradle lever 24 is pressed towards the bottle 12 as the bottle 12 is inverted to deliver one or more drops. As the free end 30 is pressed inwardly, and as shown in Figure 2, the portion 22 indents a side of the reservoir 20 adjacent to the neck 14, thus deforming the outer wall 23 and reducing the volume of the reservoir 20. As a result, one or more drops may be controllably expelled. The dosage amount may be fixed to a predetermined extent of movement of the cradle lever 24, such as by example, restricting movement of the cradle lever 24 with a stop member. Optionally, at the point where the predetermined drop(s) are expelled (i.e., at a predetermined extent of movement of the cradle lever 24), the user may be alerted to a complete dosing wherein a toe 32 of the cradle lever 24 may nest into a recess 34 defined in the lower end 26, with an audible and/or tactile 'click'

indicating that the desired drop(s) have been released from the bottle 12. Upon detecting this 'click', the user may release the free end 30 of the lever 24, which returns back to its fully open rest position (shown in Figure 1). Preferably, hinge 25 provides a biasing force to urge the lever 24 to the rest position as shown in Figure 1, where the dropper bottle 12 is undeformed or substantially undeformed. Further drops may then be released. Preferably, the hinge 25 also exerts a biasing force to press the portion 22 against the outer wall 23 without causing deformation or substantial deformation of the reservoir 20 so that unwanted dosing is avoided. To achieve this structure, the cradle 10 can be formed with the portion 22 in its natural state so as to overlap the reservoir 20. Likewise, the lower end 26 of the cradle 10 may be formed to overlap the reservoir 20.

As shown in Figure 4, and in a second aspect of the subject invention, a nozzle 100 may be provided on the dropper bottle 12 which is at least partially surrounded by a protruding outer collar 102. Preferably, the collar 102 terminates in a generally flat free end 106, and, more preferably, the free end 106 is disposed generally normally to central axis CA of the nozzle 100. Also, the collar 102 is preferably annular. The collar 102 encompasses a volume in which tip 104 of the nozzle is located. As a result, the collar 102 projects beyond the tip 104 of the nozzle 100 such that, if contact is made with an eye during use, the outer collar 102 will contact the eye and not the nozzle tip 104. The free end 106 at the front of the collar 102 will be less likely to cause the user any eye damage than the sharper nozzle tip 104. The nozzle 100 may be constructed from plastics such as polyethylene or polypropylene, or softer elastomers may be used as a further safety measure.

In a third aspect of the subject invention, a nozzle of a dropper bottle (e.g. nozzle 100) may be colored to further aid in the alignment process. As such, the nozzle 100 is non-

transparent and non-translucent and provided with a non-white color. Colors are more easily visible to the eye than the colorless plastics used in conventional dropper bottle nozzles and a colored nozzle will be easier to visually align. The nozzle 100 may also be of a different color from its associated reservoir to provide additional contrast and improved visibility of the nozzle 100. Further, colors may be used for the nozzle 100 or around the nozzle 100 to denote the contents of the dropper bottle.

As a further aid to alignment, as shown in Figure 5, nozzle 200 may be directed at an angle to aid the placement of drops into the eye. Here, discharge aperture 202 is spaced from a central axis CB of reservoir 20. Preferably, the nozzle 200 is formed symmetrically along at least a portion of a central axis CD which is angularly disposed to the central axis CB. Angle  $\alpha$  is defined between the central axes CD and CB and may be in the range of greater than  $0^\circ$  to approximately  $135^\circ$ .

In a fourth aspect of the subject invention, and with reference to Figures 6-8, a device 300 is provided which limits the degree of deformation of the dropper bottle 12 to such an amount necessary to expel one dose or drop. The device 300 includes at least one, preferably a series of, outwardly-extending webs 302, like tree branches, which project from a central column 304 that is in communication with nozzle 306 and the reservoir 20. Preferably, the central column 304 is fixed to the nozzle 306, such as by being formed integrally therewith, in forming the device 300. Any method may be used to fix the device 300 to the bottle 12 including an interference fit in the neck 14 of the bottle 12. A locking detent 308 may also be provided to enhance the fixation of the device 300 to the bottle 12.



The column 304 may optionally be formed with one or more apertures 310, as shown in Figure 8, to communicate the interior of the column 304 with the reservoir 20.

By way of non-limiting example, for installation, the device 300 may be inserted through the neck 14 with the webs 302 bending backwards through the neck 14 (Figure 6) and returning to their original shape (Figure 7) whilst in the reservoir 20 after installation. As shown in Figure 8, once installed, the webs 302 are shaped and configured to limit the amount of deformation of the outer wall 23 to a predetermined amount in limiting the amount to be dosed (Figure 8).

Although the webs 302 may be formed sufficiently resilient to pass through the neck 14, the webs 302 need sufficient strength in compression to resist buckling and excessive deformation of the outer wall 23. It is preferred that the webs 302 be disposed generally normally to the generally cylindrical portion of the outer wall 23. Also, as will be appreciated by those skilled in the art, the webs 302 can be formed as annular discs as shown in the Figures or in other various configurations and supported in any manner.

In a fifth aspect of the subject invention, and as shown in Figures 9-11, a device 400 is provided which limits the amount of liquid dispensed by a dropper bottle 12 to one drop or dose. The device 400 generally includes a check valve ball 402 which is free to run within a tube 404. The tube 404 extends from nozzle 406 and has a number of slots or openings 408 formed therethrough which allow fluid communication between inside 409 of the tube 406 and the reservoir 20. Also, the end of the tube 406 may be spaced from the outer wall 23, such as at the base 16, with the tube 404 communicating with the reservoir 20 via spacing 401. Preferably, the tube 404 is formed to continuously maintain the ball 402 therewithin.

As such, the openings 408 and the spacing 401 may be sized to not permit passage therethrough of the ball 402. The end of the tube 404 adjacent to the nozzle 406 has a first section 410 sized to receive the ball 402 therewithin so as to form a fluid seal therewith. Portions of the tube 404 adjacent the first section 410 are generally larger than the first section 410. The first section 410 communicates with discharge passage 412 of the nozzle 406 and preferably encompasses a volume at least equal to a single dose to be administered by the dropper bottle 12.

In use, the ball 402 drops to the bottom of the bottle 12 when the bottle is upright and rested on its base 16 (Figure 9). As the bottle 12 is inverted for use (with the nozzle 406 being directed downwards) (Figures 10-11), liquid in the reservoir 20 enters the openings 408 to flood the inside of the tube 404, and the ball 402 drops down through the tube 404 towards the nozzle 406. As the ball 402 reaches the first section 410, the first section 410 is already flooded and fully charged with liquid (Figure 10). The ball 402 generally seals the first section 410 from remaining portions of the tube 404. By applying pressure to the wall of the reservoir 20 (such as with normal drop administration), fluid within the reservoir 20 is pressurized which forces the ball 402 through a defined stroke of the first section 410. In turn, the ball 402 displaces fluid along its path through the first section 410 resulting in an expelled drop of equal volume to the swept volume of the ball 402 (swept volume being the displaced volume during travel of the ball 402). In other words, the ball 402 generally displaces the full volume of the first section 410. As the ball 402 reaches the end of travel it will shut-off against a seat 414 and no more liquid can be expelled (Figure 11). Thereafter, the dropper bottle 12 can be righted and the process repeated.

In a sixth aspect of the subject invention, an alternative to the above means of expelling a drop by deformation of a dropper bottle is provided by a piston 500 as shown in Figures 12-13. In this configuration, the piston 500 is displaceable from an initial position as shown in Figure 12, and towards, possibly into, the reservoir 20 to an actuated position as shown in Figure 13, so as to reduce the interior volume of the dropper bottle 12.

Accordingly, a pressure rise is created in the bottle 12, and this rise in pressure causes a drop or dose to be expelled from the bottle 12 when the bottle 12 is inverted for use. As will be appreciated by those skilled in the art, the bottle 12 need not be deformable, since deformation is not required for dose administration.

The piston 500 extends through piston bore 502 which may be formed through plug 506 or the outer wall 23. To facilitate assembly, it is preferred that nozzle 508 be unitarily formed with the plug 506. The plug 506 may be fixed to the bottle 12 using any known method including an interference fit in the neck 14 of the bottle 12. A locking detent 510 may also be provided to enhance the fixation of the plug 506 to the bottle 12. Any known technique may be used to seal the piston bore 502 from leaking with the piston 500 being slidably disposed therein. For example, piston seal 517 may be provided as is known in the art to seal against the wall of the piston bore 502.

It is preferred that a spring 512 be provided to urge the piston 500 to an initial position, as shown in Figure 12. As such, after use and release of the piston 500, the piston 500 may return to its initial position and be ready for subsequent dosing. Also, a shoulder 514 may be formed at the end of the piston bore 502 to coact with stop member 516 on the piston 500 to prevent excessive rearward movement of the piston 500 under force of the

spring 512. A button 518 may further be provided on the piston 500 to provide a good surface against which a user may apply pressure in displacing the piston 500.

With reference to Figures 14-16, and as a variation of the sixth aspect of the subject invention, a device 600 is provided which includes a nozzle 602 that acts as a piston. More specifically, the nozzle 602 is displaceable within the bottle 12 to reduce the interior volume thereof. The nozzle 602 is disposed to translate within the neck 14. The nozzle 602 is formed with a discharge aperture 605 at one end in communication with an inlet opening 607 at the other end. Upon displacing the nozzle 602 downwardly to an actuated position as shown in Figure 15, pressure within the interior volume of the dropper bottle 12 is increased resulting in fluid being displaced from the interior of the dropper bottle 12 through the nozzle 602 via the inlet opening 607 and out the discharge aperture 605. Piston seal 614 may be provided to cooperate with the neck 14 in defining a seal therewith. As with the previous design, the dropper bottle 12 need not be deformable.

The nozzle 602 is preferably biased by a spring 612 to an initial state as shown in Figure 14. Shoulder 616 and stop member 618 can be provided to coact and prevent excessive rearward movement of the nozzle 602 under force of the spring 612.

Optionally, cradle 604 may be provided to facilitate actuation of the nozzle 602. The cradle 604 is preferably formed to resiliently snap about the dropper bottle 12 at the nozzle 602 and the bottle base 16, and is used to impart inward motion to the nozzle 602 (downward motion towards the base 16). To this end, a free end 606 of the cradle 604 is pressed transversely towards the bottle 12. As a result, a forked end 608 of the free end 606 translates across at least one rounded face 610 of the nozzle 602. As best shown in Figure 16, the

forked end 608 may straddle tip 609 of the nozzle 602 and provide stability of the cradle 604 relative to the dropper bottle 12. As the forked end 608 translates, the forked end 606 drives the nozzle 602 against the spring 612 (in the direction of the base 16) so that the nozzle 602 moves downwardly. This downward translation is achieved by the rotation of the forked end  
5 608 about pivot 611. The rotation in effect shortens the radius of the forked end 608 in relation to the pivot 611, thus causing increased force to be applied against the rounded face 610. The interface of rounded surfaces between the forked end 608 and the rounded face 610 is desired to limit resistant frictional forces being defined therebetween. Upon release, the spring 612 urges the nozzle 602 upwardly. The memory of pivot 611 may also urge the  
10 cradle 604 to its initial state as shown in Figure 14. It is preferred that the cradle 604 be formed of a resilient material, such as a resilient thermoplastic. To achieve a resilient holding force, the cradle 604 may be formed to overlap portions of the dropper bottle 12.

As is readily apparent, numerous modifications and changes may readily occur to  
15 those skilled in the art, and hence it is not desired to limit the invention to the exact construction operation as shown and described, and accordingly, all suitable modification equivalents may be resorted to falling within the scope of the invention as claimed.

**What is claimed is:**

1. A dropper bottle assembly comprising:

a dropper bottle including an interior volume; and,

a cradle mounted to said dropper bottle, said cradle including a movable lever arm,

5 wherein movement of said lever arm causes a first portion of said lever arm to deform said dropper bottle in reducing said interior volume of said dropper bottle, whereby reduction of said interior volume causes fluid to be administered from said dropper bottle.

2. An assembly as in claim 1, wherein said cradle includes a second portion defining a

10 recess, and a second portion being formed on said lever arm to nest within said recess upon a predetermined extent of movement of said lever arm.

3. An assembly as in claim 2, wherein said second portion of said lever arm creates an audible signal upon nesting within said recess.

15

4. An assembly as in claim 1, wherein said cradle includes a second portion, said lever arm being hingedly connected to said second portion.

5. An assembly as in claim 4, wherein said hinged connection urges said lever arm to a  
20 rest position where said dropper bottle is undeformed or substantially undeformed.

6. An assembly as in claim 4, wherein said lever arm includes a free end, said first portion of said lever arm being located intermediate said hinged connection and said free end.

7. An assembly as in claim 4, wherein said second portion includes an aperture, said dropper bottle including a neck, said aperture being larger than said neck.

8. An assembly as in claim 7, wherein said first portion of said lever arm being formed to pressingly engage said dropper bottle to cause a portion of said neck to pressingly engage said second portion of said cradle located adjacent said aperture.

9. An assembly as in claim 1, wherein said dropper bottle includes an indented bottom surface, a second portion of said cradle being formed to seat within and press against said indented bottom.

10. A dropper bottle comprising a reservoir, a nozzle in fluid communication with said reservoir, said nozzle terminating in a discharge aperture, and a collar at least partially bounding said nozzle.

11. A dropper bottle as in claim 10, wherein said collar encompasses a volume, said discharge aperture being located within said volume.

12. A dropper bottle as in claim 10, wherein said collar is annular.

13. A dropper bottle as in claim 10, wherein said collar terminates in a generally flat free end.

14. A dropper bottle as in claim 13, wherein said free end is disposed generally normally to a central axis of said nozzle.

15. A dropper bottle comprising a reservoir and a nozzle in fluid communication with said reservoir, said nozzle being non-transparent and non-translucent and being formed with a non-white color.

5 16. A dropper bottle as in claim 15, wherein said reservoir is of a different color from said nozzle.

17. A dropper bottle comprising a reservoir formed about a central axis, and a nozzle in fluid communication with said reservoir, said nozzle terminating in a discharge aperture, said  
10 discharge aperture being spaced from said central axis.

18. A dropper bottle as in claim 17, wherein said nozzle is formed symmetrically along at least a portion of a second central axis, said second central axis being angularly disposed relative to said first-mentioned central axis.

15

19. A dropper bottle comprising a reservoir, and at least one web disposed in said reservoir so as to limit deformation of said reservoir.

20. A dropper bottle as in claim 19 further comprising a nozzle, and a column in fluid  
20 communication with said reservoir and said nozzle, said at least one web extending transversely from said column.

21. A dropper bottle as in claim 20, wherein a plurality of webs extend from said column.



22. A dropper bottle as in claim 20, wherein said column is integrally formed with said nozzle.

23. A dropper bottle as in claim 20, wherein said reservoir is defined by an outer wall,  
5 said nozzle being fixed to said outer wall.

24. A dropper bottle comprising a reservoir, a nozzle in fluid communication with said reservoir, a tube in fluid communication with said reservoir and said nozzle, and, a check valve ball disposed in said tube.

10

25. A dropper bottle as in claim 24, wherein a first section of said tube configured so as to define a seal with said check valve ball, portions of said tube adjacent said first section being larger in diameter than said first section.

15 26. A dropper bottle as in claim 25, wherein said first section of said tube encompasses a volume at least equal to a dose to be administered by the dropper bottle.

27. A dropper bottle as in claim 25, wherein said first section being the most proximate portion of said tube to said nozzle.

20

28. A dropper bottle as in claim 24, wherein said tube being formed to continuously maintain said check valve ball therewithin.

29. A dropper bottle as in claim 28, wherein at least one aperture is formed in said tube to communicate said tube with said reservoir, said at least one aperture being smaller in size than said check valve ball.


5 30. A dropper bottle as in claim 28, wherein said tube extends into said reservoir and into proximity to an outer wall defining said reservoir so as to define a spacing between said tube and said outer wall, said reservoir communicating with said tube via said spacing, said spacing being sized to not permit passage therethrough of said check valve ball.

10 31. A dropper bottle comprising an interior volume, a discharge aperture in fluid communication with said interior volume, and a displaceable piston, wherein said piston is displaceable from an initial position to an actuated position, the volume of said interior volume being less with said piston in said actuated position than in said initial position, whereby reduction of said interior volume causes fluid to be administered from said dropper  
15 bottle.

32. A dropper bottle as in claim 31, wherein said piston is connected to said discharge aperture so as to be displaced in concert therewith.

20 33. A dropper bottle as in claim 31 further comprising a biasing means to urge said piston to said initial position.

1/16



2/16




FIG. 2

3/16




FIG. 3

4/16




FIG. 4

5/16




FIG. 5




FIG. 6



7/16




FIG. 7




FIG. 8

9/16




FIG. 9 16

10/16




FIG. 10

11/16





FIG. 11

12/16



13/16






FIG. 13





15/16






FIG. 16

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/US03/24484

**A. CLASSIFICATION OF SUBJECT MATTER**

IPC(7) : B65D 37/00

US CL : 222/211, 212, 213, 214, 215, 183, 160, 162, 164, 420; 604/ 295, 298

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 222/211, 212, 213, 214, 215, 183, 160, 162, 164, 420; 604/ 295, 298

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5,673,822 A (CHALMIN et al) 07 October 1997(07.10.1997), see column 3, lines 25-67 onto column 4, lines 1-65).	1,4-7
A	US 4,771,769 A (HEGEMANN et al) 20 September 1988 (20.09.1988), see Figures 1-3.	1-9
A	US 5,133,702 A (PY) 28 July 1992 (28.07.1992), see Figure 2.	1-9
A	US 6,033,384 A (PY) 07 March 2000 (07.03.2000), see Figure 2.	1-9

☐ Further documents are listed in the continuation of Box C.☐ See patent family annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&amp;" document member of the same patent family

Date of the actual completion of the international search

26 November 2003 (26.11.2003)

Date of mailing of the international search report

Name and mailing address of the ISA/US

Mail Stop PCT, Attn: ISA/US

Commissioner for Patents

P.O. Box 1450

Alexandria, Virginia 22313-1450

Facsimile No. (703)305-3230

Authorized officer

Frederick C. Nicolas

Telephone No. (703)-308-0861

Form PCT/ISA/210 (second sheet) (July 1998)

# INTERNATIONAL SEARCH REPORT

International application No.

PCT/US03/24484

## Box I Observations where certain claims were found unsearchable (Continuation of Item 1 of first sheet)

This international report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claim Nos.:  
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claim Nos.:  
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
3. ☐ Claim Nos.:  
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a)

## Box II Observations where unity of invention is lacking (Continuation of Item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:  
Please See Continuation Sheet

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☒ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.: 1-9

Remark on Protest ☐ The additional search fees were accompanied by the applicant's protest.  
☐ No protest accompanied the payment of additional search fees.

**BOX II. OBSERVATIONS WHERE UNITY OF INVENTION IS LACKING**

This application contains claims directed to more than one species of the generic invention. These species are deemed to lack unity of invention because they are not so linked as to form a single general inventive concept under PCT Rule 13.1.

In order for more than one species to be examined, the appropriate additional examination fees must be paid. The species are as follows:

- I- Species A: Figures 1-3.
- II- Species B: Figure 4.
- III- Species C: Figure 5.
- IV- Species D: Figures 6-8.
- V- Species E: Figures 9-11.
- VI- Species F: Figures 12-13.
- VII- Species G: Figures 14-16.

The claims are deemed to correspond to the species listed above in the following manner:

- Species A: Figures 1-3, claims 1-9.
- Species B: Figure 4, claims 10-16.
- Species C: Figure 5, claims 17-18.
- Species D: Figures 6-8, claims 19-23.
- Species E: Figures 9-11, claims 24-30.
- Species F: Figures 12-13, claims 31-33.

1. The species listed above do not relate to a single general inventive concept under PCT Rule 13.1 because, under PCT Rule 13.2, the species lack the same or corresponding special technical features for the following reasons: the only corresponding features among the six groups is a generic dropper bottle. This is well known in the art and does not constitute a special technical feature under PCT rule 13. Thus, there is no unity between the different groups.

**THIS PAGE BLANK (USPTO)**